CONTRAFLAM® 120

Fire rated clear tempered interlayered safety glass for interior applications

Classification

Fire resistive
This glass product withstands fire exposure to the non-fire side and protects from flames, smoke, hot gases and and limits temperature rise on the unexposed side.

Impact safety
Impact safety rated to meet the highest human impact safety ratings.

Hose Stream
This product withstands the hose stream test requirements.

Available Options

- → Protection
- → Coloring
- → Shapes
- → Matte finish
- → Screen printing
- → Extra clear
- → Noise reduction

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating	120 minutes
US / Canada Standards	ASTM E-119; NFPA 251; UL 263; CAN/ULC S101
Building code markings	W 120
Impact Safety Rating	ANSI Z97.1, CPSC 16CFR 1201 CAT II; CAN/CGSB - 12.1-M90
Application	Interior

Product	CONTRAFLAM® 120
Nominal thickness	1 9/16 in. (39 mm)
Thickness tolerance	-1/8 in. to 1/8 in. (-3 mm to 3 mm)
Weight	16 lb/ft² (78 kg/m²)
STC/OITC rating (ASTM E 413/E1332)	NPD
Visible transmittance (NFRC 200)	81%
Light reflection pL ext./int. (CIE 15)	11 % / 11 %
U-factor (BTU/h*sq.ft*deg F) (NFRC 100)	Winter: 0.614 / Summer: 0.569
Solar heat gain coefficient (NFRC 200)	0.65
Energy transmission (NFRC)	53%
Non Loadbearing Wall Assemblies: Max exposed dimensions *[Based on Intertek Spec ID 73711]*	134 in. (3404 mm); Area: 60,5 sq. ft. (5.62 m²)

**Height multiplied by width cannot exceed maximum exposed area.*
Shapes: Dimensional tolerances may vary.

© Vetrotech Saint-Gobain | July 2026

vetrotech SAINT-GOBAIN | 4G FACADE

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com