CONTRAFLAM® 60

Fire Rated clear tempered interlayered safety glass for interior applications

Classification

Fire resistive
This glass product withstands fire exposure to the non-fire side and protects from flames, smoke, hot gases and and limits temperature rise on the unexposed side.

Fire protective
This glass product withstands fire exposure to the non-fire side and protects from flames, smoke, hot gases and significantly reduces radiant heat.

Impact safety
Impact safety rated to meet the highest human impact safety ratings.

Hose Stream
This product withstands the hose stream test requirements.

Available Options

- → Protection
- → Extra clear
- → Coloring
- → Shapes
- → Matte finish
- → Screen printing

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating	60 minutes
US / Canada Standards	ASTM E-119, NFPA 80, NFPA 252, NFPA 257 - UL9, UL 10B, UL 10C, UL 263 CAN/ULC-S101, CAN/ULC-S104, CAN/ULC-S106
Intertek file number(s)	73711 / 84964
Building code markings	D-H 60; D-H-T 60; OH 60; W 60; D-H-T-W 60
Impact Safety Rating	ANSI Z97.1. CPSC 16CFR 1201-CAT II. CAN/CGSB - 12.1-M90
Application	Interior

Winter: 0.735 / Summer: 0.674	CONTRAFLAM® 60-2	CONTRAFLAM® 60-3/4
Nominal thickness	1 in. (25 mm)	1 1/8 in. (28 mm)
Thickness tolerance	± 1/16 in. (± 2 mm)	± 1/16 in. (± 2 mm)
Weight	10 lbs/sq. ft. (50 kg/m²)	12 lb/ft² (59 kg/m²)
STC/OITC rating (ASTM E 413/E1332)	42 / 38 calculated	43/39 calculated
Visible transmittance (NFRC 200)	85%	84%
Light reflection pL ext./int. (CIE 15)	9 % / 9 %	10 % / 10 %
U-factor (BTU/h*sq.ft*deg F) (NFRC 100)	Winter: 0.735 / Summer: 0.674	Winter: 0.727 / Summer: 0.668
Solar heat gain coefficient (NFRC 200)	0.7	0.68
Energy transmission (NFRC)	60%	58%
Door. Non-Temp Rise: Max exposed w x h. a Max exposed dimensions *[Based on Intertek Spec ID 84964]*	30 in. x 89-1/2 in.. 2685 sq. in. (0.76 m x 2.27 m. 1.73 m²)	
Door. Temp Rise: Max exposed w x h. a* Max dimensions *[Based on Intertek Spec ID 84964]*	30 in. x 89-1/2 in.. 2685 sq. in. (0.76 m x 2.27 m. 1.73 m²)	
Windows. Transom. Sidelite: Max exposed w x h. a* Max exposed dimensions *[Based on Intertek Spec ID 84964]*	94-13/16 in. x 94-13/16 in.. 4449 sq. in. (2.41 m x 2.41 m. 2.87 m²)	
Non Loadbearing Wall Assemblies: Max exposed dimensions *[Based on Intertek Spec ID 73711]*	94-13/16in. (2408 mm) Area: 30,9 sq. ft. (2.87 m²)	

**Height multiplied by width cannot exceed maximum exposed area.*
Shapes: Dimensional tolerances may vary.
Dimensions provided are based on general protective rated listing.

© Vetrotech Saint-Gobain | July 2026

vetrotech SAINT-GOBAIN | 4G FACADE

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com