CONTRAFLAM® One 120 US/C

Fire-rated clear tempered interlayered safety glass for interior applications

Classification

Fire resistive
This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat and hot gases.

Impact safety
Impact safety rated to meet the highest human impact safety ratings.

Hose Stream
This product has passed a hose stream test.

Available Options

→ Extra clear

→ Patterned glass

→ Double glazing

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

HYBRIDCORE TECHNOLOGY™

Fire Rating	120 minutes
US / Canada Standards	UL 263; ASTM E119, E2226; CAN/ULC S101
Building code markings	W 120
Impact Safety Rating	ANSI Z97.1; CPSC 16CFR 1201-CAT II; CAN/CGSB - 12.1-M90
Application	Interior

Product	CONTRAFLAM® One 120 US/C	
Glass Type	Planiclear	Diamant
Nominal thickness	1-7/16 in. (37 mm)	1-7/16 in. (37 mm)
Thickness tolerance	± 5/64 in. (± 2 mm)	± 5/64 in. (± 2 mm)
Weight	12.1 lbs/sq. ft. (59 kg/ m²)	12.1 lbs/sq. ft. (59 kg/ m²)
STC/OITC rating (ASTM E 413/E1332)	41 / 41 measured	41 / 41 measured
Visible transmittance (NFRC 200)	87%	89%
Light reflection pL ext./int. (CIE 15)	8% / 8%	8% / 8%
U-factor (Btu/h*sq.ft*deg F) (NFRC 100)	Winter: 0.789 / Summer: 0.738	Winter: 0.789 / Summer: 0.738
Solar heat gain coefficient (NFRC 200)	0.68	0.71
Energy transmission (NFRC 300)	57%	61%
Non Loadbearing Wall Assemblies: Max dimensions *[Based on Intertek Spec ID 73711]*	126-3/16 in. (3206mm); Area: 45.1 sq. ft. (4.19 m²)	126-3/16 in. (3206mm); Area: 45.1 sq. ft. (4.19 m²)
Temperature range	-40°C/ +60°C (-40°F / + 140 °F)	-40°C/ +60°C (-40°F / + 140 °F)

Additional Information to CONTRAFLAM 120-1
Exterior applications might be possible, please contact us.

© Vetrotech Saint-Gobain | December 2025

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com