VDS® 120 Framing System by 4G FACADE

Vetrotech Design Solutions Fire-Rated Framing System

Classification

Fire-Resistive
This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat, and hot gases.

Fire-Rated System
This system solution brings together framing, doors, and glazing for an all-in-one fire-rated barrier. Complement with 90-minute doors.

Hose Stream Tested
This product has passed a hose stream test.

Available Options

→ Protection

→ Finish Color

→ Noise Reduction
→ Interior / Exterior

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating	120 minutes
US / Canada Standards	ASTM E119, UL 263, CAN/ULC-S101, LARR 26129 Can be customized to meet up to Level 3, per UL 752
Application	Interior / Exterior

Product	VDS 120
Finish Options	Enamel / Powder Coat, custom colors available
Fabrication	Knock-Down standard, welded option available
Weight	6.7 lbs/lin. ft. (10 kg/lin. m) (does not include glass)
Glazing Options	CONTRAFLAM 120 and CONTRAFLAM Structure 120
Door Type	Single/Double Doors

Product characteristics are subject to change without notice and may vary depending on manufacturing size and composition. Available options are dependent on product type and application.

vetrotech SAINT-GOBAIN

4G FACADE

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com