VDS® 60 Framing System by 4G FACADE

Vetrotech Design Solutions Fire-Rated Framing System

Classification

Fire-Resistive
This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, radiant heat, and hot gases.

Fire-Rated System
This system solution brings together framing, doors, and glazing for an all-in-one fire-rated barrier. Complement with 60-minute doors.

Hose Stream Tested
This product has passed a hose stream test.

Available Options

→ Protection

→ Finish Color

→ Noise Reduction
→ Interior / Exterior

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating	60 minutes
US / Canada Standards	ASTM E119, UL 263, CAN/ULC-S101, LARR 26129 Can be customized to meet up to Level 3, per UL 752
Application	Interior / Exterior

Product	VDS 60
Finish Options	Enamel / Powder Coat, custom colors available
Fabrication	Knock-Down standard, welded option available
Weight	4 lbs/lin. ft. (6 kg/lin. m) (does not include glass)
Glazing Options	CONTRAFLAM 60 and CONTRAFLAM Structure 60
Door Type	Single/Double Doors

Product characteristics are subject to change without notice and may vary depending on manufacturing size and composition. Available options are dependent on product type and application. Contact your 4G Facade representative for further support.

© Vetrotech Saint-Gobain | SEPT 2026

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com