VDS® Doors by 4G FACADE

Vetrotech Design Solutions Fire-Protective Door System

Classification

Fire-Resistive
This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, and hot gases.

Temperature Rise
Only applicable to fully glazed doors with CONTRAFLAM 60 or 90 installed.

Fire-Rated System
This system solution brings together framing, doors, and glazing for an all-in-one fire-rated barrier.

Hose Stream Tested
This product has passed a hose stream test.

Available Options

- → Smoke door
- → Noise reduction
- → Interior / Exterior
- → Finish color
- → Hardware
- → Split lite door
- → Full lite door
- → Oversized door

Approved installation in VDS Curtain Wall, VDS, and VDS Lite framing systems.

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating	45 / 60 / 90 minutes
US / Canada Standards	NFPA 80/252, UL 10 B/10 C, ANSI/ UL 1784, CAN/ULC-S104, LARR 26129
Application	Interior / Exterior

Product	VDS Doors
Finish Options	Enamel / Powder coat, custom colors available
Fabrication	Welded
Weight	5-7 lbs/lin. ft. (7.4-10.4 kg/lin. m) (does not include glass, weight per unit provided before shipping)
Glazing Options	CONTRAFLAM 45 / 60 / 90
Door Type	Single / Double doors
Door Leaf Maximum (w x h)	Single Door, 60-min: 57 in. x 121-1/2 in. Double Doors, 60-min: 114 in. x 121-1/2 in. Single Door, 90-min: 48 in. x 96 in. OR 42 1/2 in. x 99 1/2 in. Double Doors, 90-min: 96 in. x 96 in. OR 86 7/16 in. x 99 1/4 in.

Product characteristics are subject to change without notice and may vary depending on manufacturing size and composition. Available options are dependent on product type and application.

© Vetrotech Saint-Gobain | SEPT 2026

vetrotech SAINT-GOBAIN

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com