VDS® Lite by 4G FACADE

Vetrotech Design Solutions Fire-Protective Window System

Classification

Fire-Protective
This glass product can withstand fire exposure to the non-fire side and protects from flames, smoke, and hot gases.

Fire-Rated System
This system solution brings together framing, doors, and glazing for an all-in-one fire-rated barrier. Complement with 45 / 60 / 90 minute doors.

Hose Stream Tested
This product has passed a hose stream test.

Available Options

→ Protection

→ Finish color

→ Noise reduction
→ Interior / Exterior

Contact us for a personalized solution to meet your product requirements.

Technical Specifications

Fire Rating	45 / 60 / 90 minutes
US / Canada Standards	NFPA 257, UL 9, CAN/ULC-S106, LARR 26129
Application	Interior / Exterior

Product	VDS Lite
Finish Options	Enamel / Powder coat, custom colors available
Fabrication	Knock-Down is standard, fully welded option available
Weight	2 lbs/lin. ft. (3 kg/lin. m) (does not include glass)
Glazing Options	CONTRAFLAM 45 / 60, KERALITE V-NIX Filmed or Laminated 45 / 60 / 90, PYROSWISS 45
Door Type	Single / Double doors

© Vetrotech Saint-Gobain | SEPT 2026

Product characteristics are subject to change without notice and may vary depending on manufacturing size and composition. Available options are dependent on product type and application.

vetrotech SAINT-GOBAIN

4G FACADE
PO Box 122 / Cedar Rapids IA / 52406
(800) 553-8134
info@4GFACADE.com
4GFACADE.com